

55532 UNIVERSAL TRACTOR FLUID

MOLEC[®] 55532 Universal Tractor Fluid is a multi-functional tractor hydraulic fluid, specially formulated for use in transmissions, final drives, wet brakes and hydraulic systems of tractors and other equipment employing a common fluid reservoir.

MOLEC[®] 55532 Universal Tractor Fluid is formulated with high-quality base oils, a shear stable viscosity index improver, oxidation and corrosion inhibitors, anti-foaming agents, anti-wear additives and a pour point depressant to exceed the performance and protection requirements of tractors and other farm equipment used in North America

TECHNICAL DATA:

SPECIFICATIONS	ASTM	55532 UTF
Product Number		55532
Viscosity @ 100°C, cSt	D7042	9.42
Viscosity @ 40°C, cSt		61.9
Viscosity Index	D2270	132
Specific Gravity @ 60°F	D1298	0.865
Pour Point, °C	D97	-39
Brookfield Viscosity @ -35°C, Cp	D2893	53,500
Colour ASTM	D1500	Clear & Bright

BENEFICIAL QUALITIES:

- Superior friction durability
- Superior load carrying and wear protection
- Enhanced yellow metal protection
- Excellent oxidation and deposit control for improved cleanliness
- Proven Field Performance Technology
- Advanced corrosion protection even in presence of moisture
- Provides wide operating temperature range for summer and all but the most severe winter operations.

MEETS OR EXCEEDS THE FOLLOWING INDUSTRY & OEM SPECIFICATIONS*:

- API: GL-4*
- Allison: C2, C3, C-4**
- AGCO: Power Fluid 821XL
- Caterpillar: TO-2
- CNH MAT 3510, 3525, 3540
- Deutz-Allis Power Fluid: 821XL, 25741, 25743, 246634, 272843
- Fiat Heston: AF-87
- Ford: ESN-M2C-86 A,B & C, FNHA-2-C-200, CNHA-2-C-201, ESN-M2C134A-D (NH-410B), ESN-M2C-77A, 78A, 79A.
- International Harvester Hy-Tran B-6
- Japanese Construction Mechanization Association (JCMAS), HK P-041
- J.I. Case: Case-O-Matic Type A
- John Deere: J20A, J20C, J14A-C, JTD 303, J21A
- Kioti: Tractor
- Kubota: Super UDT, Super UDT2
- Landini: Tractor
- Massey Ferguson: 1103A&B, M1110, 1127, 1127A&B, M1129, M1129A (Permatran) M1139 (UTTO only, not STOU), M1144 (UTTO only, not STOU)
- New Holland: 410B, 410C, 420A
- Valmet: Tractor
- Wet Brake Applications
- Yanmar: Tractor

* API GL-4 is an automotive gear lubricant specification, and this product is not recommended for use in hypoid applications

**Allison no longer recommends Tractor Hydraulic Fluids in their transmissions

AVAILABLE PACKAGING: • 18.9L Pails • 205L Drums • 1000L Totes

PRODUCT CODES: 55532

WHEN QUALITY MATTERS[®]

MOLEC Lubricants takes no responsibility for product misuse or misapplication. Always follow OEM recommendations for fluid viscosity and API Service category.

Molec Lubricants: Plamondon, Alberta, Canada T0A 2T0 • www.moleclubricants.com • (780) 798-2224