

SECTION 1 Identification**1.1. GHS Product identifier**

Product form : Mixture
Trade name : ASTO-4 PREMIUM DRIVETRAIN FLUID
Product code : 50896

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : ALL-SEASON TORQUE FLUID
Restrictions on use : None known

1.4. Supplier's details

MOLEC LUBRICANTS
68567 HWY 858
PLAMONDON, AB T0A 2T0
Canada
T 780-798-2224
sds@moleclubricants.com

1.5. Emergency phone number

Emergency number : For Hazardous Materials or Dangerous Goods Incident Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night: 1-800-424-9300 (Toll Free, USA) / 703-527-3887 (Virginia, USA)
CCN 997999
Back-up Emergency Number: +1 703-741-5970 (Washington, DC)

SECTION 2 Hazard identification**2.1. Classification of the substance or mixture****Classification (GHS CA)**

Reproductive toxicity, Category 1B H360 May damage fertility.
Full text of H statements : see section 16

2.2. GHS label elements, including precautionary statements**GHS CA labeling**

Hazard pictograms (GHS CA) :



Signal word (GHS CA) : Danger
Hazard statements (GHS CA) : May damage fertility.
Precautionary statements (GHS CA) : Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves, protective clothing, eye and face protection.
IF exposed or concerned: Get medical advice or attention.
Store locked up.
Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

ASTO-4 PREMIUM DRIVETRAIN FLUID

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Highly refined mineral oil	Distillates (petroleum), solvent-dewaxed heavy paraffinic	CAS-No.: 64742-65-0	2.655 – 4.425	Acute Tox. 4 (Inhalation:dust,mist), H332 Aquatic Chronic 4, H413
Zinc Dialkyldithiophosphate	Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts	CAS-No.: 85940-28-9	0.44 – 1.32	Aquatic Chronic 2, H411
Phenol, (tetrapropenyl) derivatives	Phenol, (tetrapropenyl) derivs.	CAS-No.: 74499-35-7	0.088 – 0.132	Skin Corr. 1C, H314 Eye Dam. 1, H318 Repr. 1B, H360 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Comments : The concentration ranges are provided due to batch-to-batch variability.

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin areas with mild soap and water, followed by warm water rinse. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical advice/attention if you feel unwell.
First-aid measures general	: First aider: Pay attention to self-protection. Never give anything by mouth to an unconscious person. Give artificial respiration if necessary. Induce artificial respiration with mask fitted with one-way valve or other suitable device but, not mouth-to-mouth. Call a poison center/doctor/physician if you feel unwell.

ASTO-4 PREMIUM DRIVETRAIN FLUID

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.
Chronic symptoms	: May damage fertility.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: IF exposed or concerned: Get medical advice/attention.
-----------------------------------	--

SECTION 5 Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Dry chemical, CO2, or water spray or regular foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: The product is not flammable.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO2).

5.3. Special protective actions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. Move containers from fire area if it can be done without personal risk. Use water spray or fog for cooling exposed containers. Large fires: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Withdraw immediately in case of rising sound from venting devices or discoloration from tank. ALWAYS stay away from tanks engulfed in fire. For a massive fire, use unmanned hose holders or monitor nozzles, or withdraw from the area and allow fire to burn. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid all personal contact including breathing in the mist, spray, vapors. Do not take actions involving personal risks. Absorb spillage to prevent material-damage. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.
Environmental precautions	: Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment	: Contain with non-combustible inert absorbent. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
-----------------	---

ASTO-4 PREMIUM DRIVETRAIN FLUID

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

Methods for cleaning up : Take up in non-combustible inert absorbent and place into container for disposal. Contaminated absorbent material may pose the same hazard as the spilled product. Decontaminate surfaces and equipment with water and detergent. Until a sufficient level of dilution is achieved, the decontamination water may pose the same hazards as the product. Notify authorities if product enters sewers or public waters. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

For further information refer to section 8: "Exposure controls/personal protection", For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Wear personal protective equipment. Do not breathe mist, spray, vapors. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

Additional hazards when processed : If spilled, may cause the floor to be slippery.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep away from food, drink and animal feeding stuffs.

Incompatible materials : Oxidizing agents.

Heat-ignition : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Packaging materials : Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Handle in accordance with good industrial hygiene and safety procedures. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Environmental exposure controls : Avoid release to the environment. Take measures to reduce or limit air emissions and releases to soil and the aquatic environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment:

Personal protective equipment should be chosen according to national standards and in discussion with the supplier of the protective equipment. Wear recommended personal protective equipment.

Hand protection:

Wear protective gloves. Wear suitable gloves resistant to chemical penetration

Eye protection:

Wear safety glasses which protect from splashes

ASTO-4 PREMIUM DRIVETRAIN FLUID

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

Skin and body protection:

Body protection should be chosen depending on activity and possible exposure

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Slightly hazy.
Color	: Pale yellow
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 220 °C / 428 °F
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.8607
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: > 45 mm²/s
Explosion limits	: No data available
Particle characteristics	: No data available

Highly refined mineral oil

Particle characteristics	No data available
--------------------------	-------------------

Zinc Dialkyldithiophosphate

Particle characteristics	No data available
--------------------------	-------------------

Phenol, (tetrapropenyl) derivatives

Particle characteristics	No data available
--------------------------	-------------------

ASTO-4 PREMIUM DRIVETRAIN FLUID

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions of use.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Keep container closed when not in use. Keep separate from food, feedstuffs, fertilizers and other sensitive material. Incompatible materials.
Incompatible materials	: Oxidizing agents.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce: Carbon oxides (CO, CO ₂). Irritating fumes.
Hardening time:	: No additional information available

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified.

Highly refined mineral oil

LD50 oral rat	> 5000 mg/kg body weight
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg body weight
LC50 Inhalation - Rat	> 5.53 mg/l/4h
LC50 Inhalation - Rat (Dust/Mist)	2.18 mg/l

Zinc Dialkyldithiophosphate

LD50 oral rat	3080 mg/kg
LD50 dermal rabbit	> 20000 mg/kg body weight
LC50 Inhalation - Rat	> 2.3 mg/l air

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: May damage fertility.
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

Highly refined mineral oil

LOAEL (oral,rat,90 days)	125 mg/kg body weight
NOAEC (inhalation,rat,dust/mist/fume,90 days)	> 0.98 mg/l air

Zinc Dialkyldithiophosphate

NOAEL (oral,rat,90 days)	125 mg/kg body weight
--------------------------	-----------------------

ASTO-4 PREMIUM DRIVETRAIN FLUID

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

Aspiration hazard : Not classified

ASTO-4 PREMIUM DRIVETRAIN FLUID

Viscosity, kinematic : > 45 mm²/s

Symptoms/effects after inhalation : Not expected to present a significant inhalation hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : Not expected to present a significant skin hazard under anticipated conditions of normal use.

Symptoms/effects after eye contact : Not expected to present a significant eye contact hazard under anticipated conditions of normal use.

Symptoms/effects after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

Chronic symptoms : May damage fertility.

SECTION 12 Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term : Not classified
(acute)

Hazardous to the aquatic environment, long-term : Harmful to aquatic life with long lasting effects
(chronic)

Highly refined mineral oil

LC50 - Fish [1] : > 5000 mg/l

EC50 - Crustacea [1] : > 1000 mg/l

EC50 96h - Algae [1] : > 1000 mg/l

Zinc Dialkyldithiophosphate

LC50 - Fish [1] : 4.5 mg/l

EC50 - Crustacea [1] : 5.4 mg/l

ErC50 algae : 2.1 mg/l

EC50 72h - Algae [1] : 2.1 mg/l

EC50 96h - Algae [1] : 2.1 mg/l

EC50 96h - Algae [2] : 2 mg/l

Phenol, (tetrapropenyl) derivatives

LC50 - Fish [1] : 0.146 mg/l

EC50 96h - Algae [1] : 0.6 mg/l

12.2. Persistence and degradability

ASTO-4 PREMIUM DRIVETRAIN FLUID

Persistence and degradability : Not established.

Highly refined mineral oil

Persistence and degradability : Not rapidly degradable

Zinc Dialkyldithiophosphate

Persistence and degradability : Not rapidly degradable

ASTO-4 PREMIUM DRIVETRAIN FLUID

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

Phenol, (tetrapropenyl) derivatives

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

12.3. Bioaccumulative potential

Highly refined mineral oil

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6
---	---------

Zinc Dialkyldithiophosphate

Partition coefficient n-octanol/water (Log Pow)	8.87
---	------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations. Dispose of this material and its container at hazardous or special waste collection point. Refer to all applicable national, international and local regulations or provisions.
Additional information	: Do not re-use empty containers.
Ecological waste information	: Avoid release to the environment.

SECTION 14 Transport information

In accordance with TDG / IMDG / IATA

TDG	IMDG	IATA
14.1. UN Number		
Not regulated for transport		
14.2. UN Proper Shipping Name		
Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)		
Not regulated	Not regulated	Not regulated
14.4. Packing group, if applicable		
Not regulated	Not regulated	Not regulated
14.5. Environmental hazards		
Not regulated	Not regulated	Not regulated
No supplementary information available		

ASTO-4 PREMIUM DRIVETRAIN FLUID

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

14.6. Special precautions for user

TDG

Not regulated

IMDG

Not regulated

IATA

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78⁹ and the IBC Code¹⁰

Not applicable

SECTION 15 Regulatory information

Highly refined mineral oil (64742-65-0)

Listed on the Canadian DSL (Domestic Substances List)

Zinc Dialkyldithiophosphate (85940-28-9)

Listed on the Canadian DSL (Domestic Substances List)

Phenol, (tetrapropenyl) derivatives (74499-35-7)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Highly refined mineral oil (64742-65-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Zinc Dialkyldithiophosphate (85940-28-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Phenol, (tetrapropenyl) derivatives (74499-35-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

SECTION 16 Other Information

Issue date : 07-14-2026

Full text of hazard classes and H-statements:

H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H332	Harmful if inhaled
H360	May damage fertility or the unborn child

ASTO-4 PREMIUM DRIVETRAIN FLUID

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

Full text of hazard classes and H-statements:	
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.