

CHAIN OIL

MOLEC[®] CHAIN OIL comes in two grades for optimal year-round performance. **LIGHT/WINTER** is a winter grade of oil designed to stay-in-place with better cold weather flow properties. **ALL SEASON** is recommended for hot spring/summer/fall and moderate winter conditions. These premium quality fluids are formulated with dedicated top-tier base oils and an excellent tackifier additive that improves adhesion and resist's "sling-off" as well as special friction, rust, corrosion and wear reducing additives. These chain oils have been developed specifically for use in the logging industry, to prevent wear on mechanical harvesters equipped with bars and chains, although they can be used for all chain and bar applications, as well as chain conveyors and drive chains that require extreme pressure qualities and stay-in-place performance.

TECHNICAL DATA:

SPECIFICATIONS	WINTER	ALL-SEASON
Product Number	50677	50680
Density (Kg/L)	0.850	0.861
Kinematic Viscosity, cSt @ 40°C	39	92.5
Kinematic Viscosity, cSt @ 100°C	7.0	12.3
Viscosity Index	130	125
Flash Point (°C)	210	220
Pour Point (°C)	-45	-36
Colour	Red	Red

APPLICATIONS:

- All chain & bar applications – mechanical & hand saw
- Chain conveyors
- Drive chains that require an Extreme Pressure non-drip lubricant

HEALTH AND SAFETY:

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDS's are available upon request. This product should not be used for purposes other than its intended use.

If disposing of used product, take care to protect the environment. As with all cleaning and maintenance procedures, run-off from the cleaning or maintenance process should be diverted into a collection vessel and not allowed to soak into the ground or enter a storm sewer. If this product is spilled or contaminated and cannot be used, creating the need for disposal, wipe up or scrape up product and deposit in a sealable container. Thoroughly clean area with detergent solutions and rinse well with water

AVAILABLE PACKAGING: • 3.78L Jugs • 18.9L Pails • 1040L Totes

PRODUCT CODES: 50680 All Season • 50677 Light/Winter

WHEN QUALITY MATTERS[®]

MOLEC Lubricants takes no responsibility for product misuse or misapplication. Always follow OEM recommendations for fluid viscosity and API Service category.

Molec Lubricants: Plamondon, Alberta, Canada T0A 2T0 • www.moleclubricants.com • (780) 798-2224